










HRV DESCRIPTION

Model	Dimensions H x W x D (in)	Airflow CFM (L/s)			Apparent Sensible Effectiveness (ASE) @0°C (32°F)	Sensible Recovery Efficiency (SRE) @0°C (32°F)	Performance Highlights	
		.2 (50 PA)	.3 (75 PA)	.4 (100 PA)				
95 MAX*	Recirculating Defrost 25 x 18.5 x 16	66 (31)	64 (30)	59 (28)	88% 60 CFM (28 L/s)	75% 60 CFM (28 L/s)	Top port, compact unit. Ideally suited for tight installations. Highest efficiency in its class.	
100 ECM*	Recirculating Defrost 18.75 x 33.62 x 14.75	143 (68)	129 (61)	114 (54)	78% 64 CFM (30 L/s)	71% 64 CFM (30 L/s)	Features a highly efficient energy saving ECM motor, door port balancing and the new high efficiency HEX core.	
155 MAX*	Recirculating Defrost 18.75 x 33.62 x 14.75	163 (77)	146 (69)	132 (62)	84% 64 CFM (30 L/s)	75% 64 CFM (30 L/s)	Horizontal model with door port balancing. Featuring the new high efficiency HEX core. Also available in reverse design (155 MAX-RX).	
205 MAX*	Recirculating Defrost 18.75 x 33.62 x 15	193 (91)	183 (86)	171 (81)	85% 64 CFM (30 L/s)	71% 64 CFM (30 L/s)	Top port design for flexible installations with door port balancing featuring the new high efficiency HEX core.	
COMING SOON								
267 MAX*	Recirculating Defrost 18.75 x 33.62 x 15	273 (129)	267 (126)	261 (123)	80% 64 CFM (30 L/s)	75% 64 CFM (30 L/s)	Highest airflow available in a single core ECM powered HRV. Offers maximum heat recovery and efficiency. Ideal for large custom homes and fully dedicated installations.	
195 DCS*	Damper Defrost 18.75 x 49 x 14.75	195 (92)	181 (85)	158 (74)	86% 114 CFM (54 L/s)	82% 73 CFM (35 L/s)	Horizontal model with 5th port. Dual core system for maximum heat recovery and energy efficiency. Side ducted.	
195 ECM*	Damper Defrost 18.75 x 49 x 14.75	199 (94)	191 (90)	180 (85)	85% 103 CFM (49 L/s)	79% 64 CFM (30 L/s)	Dual core system combined with an ECM motor for maximum heat recovery and energy efficiency.	
300 DCS*	Damper Defrost 18.75 x 49 x 14.75	212 (100)	202 (95)	183 (86)	90% 117 CFM (55 L/s)	79% 117 CFM (55 L/s)	Horizontal model with 5th port. Dual core model for maximum heat recovery and energy efficiency. Side ducted.	

*This product earned the ENERGY STAR by meeting strict energy efficiency guidelines set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.

INCLUDED ACCESSORIES

**DIGITAL
WALL
CONTROL**
 | DXPL02
**Included**

- 5 speed fan setting
- Stand by setting (fan speed 0)
- Electronic Dehumidistat
- 20/40/60 HIGH speed override button
- Compatible with 99-DET02 Wireless Timers
- Easy to read backlit LCD screen
- Slim-line design
- Connect to 3 wire 20 gauge low voltage wire
- Service indicator and reset button
- Five selectable modes of operation
 - Continuous Ventilation
 - 20 min. Ventilation/40 min. Recirculation
 - 20 min. Ventilation/40 min. OFF
 - 10 min. Ventilation/50 min. OFF
 - Continuous Recirculation

**HANGING
STRAPS**

| 99-80-102



- INCLUDED with all MAX & RNC products (except Metro models)
- Easy mount system enables pre-assembly on floor
- Adjustable clip simplifies leveling procedure

Visit us at
WWW.LIFEBREATH.COM

Manufacturer reserves the right to change specifications without notice.
 Printed in Canada.



*This product earned the ENERGY STAR by meeting set by Natural Resources Canada and the US EPA. This meets ENERGY STAR requirements only when used in Canada.



OPTIONAL TIMERS**TIMER OPTIONS****20/40/60 MINUTE
TIMER | DET01**

- Initiates high speed operation for 20, 40 or 60 minutes

**WIRELESS TIMER
| 99-DET02**

- Initiates high speed operation for 20, 40 or 60 minutes
- Wireless timers have an estimated range of 40ft
- Compatible with Repeater (99-RX02) for extended range
- Saves on installation time and cost
- Can be surface or E-box mounted
- Includes battery

**REPEATER | 99-RX02**

- Extends range between wireless timer (DET02) and the main control
- Plugs directly into outlet and connects wirelessly to the control and timer

OPTIONAL ACCESSORIES**DUAL HOOD
| 99-190, 99-194**

- Available with 4 in. or 5 in. hoods, requires one 6 in opening

**WEATHERHOOD KITS
| 99-185, 99-186,
99-187**

- Two 5 in diameter hoods with 12 in. sleeve and collar (also available in 6 in. and 7 in.)

**TECHGRILLE™
| 99-EAG4, 99-EAG5,
99-EAG6, 99-EAG8**

- Fully adjustable Grille with metal compression spring clips to snap in to fittings. Available in 4 in., 5 in., 6 in. or 8 in. sizes

**TERMINATOR
FITTINGS
| 99-TM4, 99-TM5,
99-TM6**

- Suitable for wall or ceiling installations, compatible with all Lifebreath Techgrille sizes. Available in 4 in., 5 in. or 6 in. sizes

**STACK HEAD ELBOW
| 99-WF4, 99-WF6**

- Available in 4 in. and 6 in. Tech Grille. Fits neatly in 2 in. x 4 in. & 2 in. x 6 in. walls

**KITCHEN GRILLE
| 10-002, 10-002-2**

- 6 in. x 10 in. hinged kitchen exhaust grille, includes one aluminum filter

**6 IN. QUICK
MOUNT FITTING
| 99-QM6**

- Simple to install, suitable for ceiling or wall applications

**6 IN. SUSPENDED
CEILING FITTING
| 99-CF6**

- Complements Tech Grille, ceiling wall fitting requires one 6 in. opening